



- 32 Mega pixels Digital Camera
- 4K/10FPS, 2.7K/20FPS, 1080P/30FPS, video
- 8 months Standby time
- 20m range of IR flash
- Triggering time: 0.2 Second
- 20m triggering distance
- Wifi module
- Remote control
- Spray-water protected (IP protection class 56)

Product Specification	
Product Name	WiFi Trail Camera
Model	HC-3
SKU	7792
Specification	
Image sensor	8 Mega pixels CMOS sensor
Image resolution	48MP:32MP(6480x4860P), 20MP:5200x3900, 16MP:4608x3456, 12MP:4000x3000, 8M:3264x2448, 5M:2592x1944, 3M:2048*1536, 1M:1280*960
Video resolution	3840x2160/10fps, 2688x1520/20fps, 1920x1080/30fps, 1280x720/60fps, 1280x720/30fps, 720x480/30fps, 640x480/30fps, 320x240/30fps
File format	JPG/AVI
Lens angle	f=3.3mm, F/NO 2.0, FOV=105, Auto IR filter
LCD Display	2.4"TFT 720*320
Memory	External memory(TF card, Class 6 Above, up to 512GB)
Operation keypad	8 Keys
Wifi module	Yes
The number of IR lamp	2PCS High power
Range of IR flash	20m
Triggering distance	65ft/20m (Below 77°F/25°C at the Normal Level)
PIR sensitivity	High/Normal/Low
Prep PIR sensing angle	Main PIR(60°) + side PIR=120°
Triggering time	0.2 Second
Trigger interval	5sec. - 60min, Programmable
Shooting numbers	1/2/3/6/10,
Video Length	3sec-10Minutes., Programmable
Effectiveness	Daytime:1.5m-infinite, Night time:1.5m-20m
Camera+Video	First take Picture then Video
Time stamp	On/Off, Include serial No., temperature and moon phase
Time lapse	On/Off, Time Lapse Programmable
Compressed video	TL Video Time Laps 3 Second ~ 24Hours
Endless Capture	On/Off, (when On, the earliest documents will be deleted when the memory card is full)
Target Recording Time1	Time Laps 1 Second ~ 24Hours
Target Recording Time2	Time Laps 1 Second ~ 24Hours
Device serial No.	4 digits set by yourself
Build-in Microphone/Speaker	Yes
Auto-distinguish images	Color images in daytime/black & white night images
Automatic screen saver	Automatic screen saver in 2 minutes while no keypad controlling
TV-out	Yes
PC interface	Mini USB2.0
Power supply	4xAAA, Expandable to 8xAAA, external 6V power supply, at least 1.5A
Standby time	approx.12 months
Lockable	Optional
Password protection	4-Digit Numbers
Spray-water protected	Spray-water protected
Physical	
Dimensions & Weight	approx.136*90*76mm / 260g
Operation Temperature	-20°C to +60°C
Storage Temperature	-30°C to +70°C